

# Smart Interactive Display

MW3575-M-S



## Specifications

Model	MW3575-M-S
Panel	
Panel size	75 inches
Resolution	3840*2160
Aspect Ratio	16:9
Brightness (cd/m <sup>2</sup> )	350
Contrast ratio	1200:1
Response time (ms)	8
Color support	1.07B
Viewing angle (H/V)	178°/178°
Android	
CPU	RK3588, quad-core Cortex-A76+quad-core Cortex-A55
GPU	ARM Mali-G610 MC4

RAM/ROM	DDR4: 16GB EMMC:256GB
Android version	Android 13.0
<b>Touch</b>	
Touch control	Infrared touch screen, 20-point multi-touch
Touch precision (mm)	±1
Glass	4mm tempered glass, level 7 on Mohs hardness scale, anti-glare
Response time (ms)	≤5
Touchscreen input	Opaque objects (e.g. finger, pen, etc.)
<b>Interface</b>	
Front interface	3*USB 3.0、1*TYPE C、1*TOUCH USB、1*HDMI IN
Rear interface	1*Line OUT、2*RJ45、1*PC Audio IN、1*VGA、1*USB 2.0、1*OPTICAL OUT、1*RS232、3*TOUCH、2*TYPE C、3*HDMI IN、1*HDMI OUT、1*DP IN、2*USB 3.0
<b>Audio</b>	
Speaker	2*15W
<b>Camera &amp; Microphone</b>	
Pixel	1300W
Viewing angle	120°
Microphone array	8
Pickup distance	8
<b>NFC function</b>	
NFC	Support NFC screen projection
<b>WiFi</b>	
WiFi	Support WiFi6
Operating Frequency	Wi-Fi STA : IEEE802.11a/b/g/n/ac/ax Wi-Fi AP : IEEE802.11 b/g/a/n/ac
<b>OSD</b>	
Language supported	Simplified Chinese, English, and others Language
<b>VESA</b>	
Wall mount hole (mm)	600*400mm
<b>General</b>	
Power supply	AC 100~240V, 50/60Hz
Maximum power consumption (W)	≤260
Standby power consumption (W)	<0.5

Operating temperature	0 to 40°C
Operating humidity	10% to 85% (non-condensing)
Storage temperature	-20 to 60°C
Storage humidity	5% to 90% (non-condensing)
Product dimensions (W*H*D)(mm)	1706*1015.1*84.1mm
Package dimensions (W*H*D)(mm)	1836.1*1141.7*230mm
Weight (kg)	Net weight:61 Gross weight:71
Accessories included	1* wall mount, 1* remote control, 2*Touch pen, 1* Quick Start,

**Zhejiang Uniview Technologies Co.,Ltd.**

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2022 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.