

Smart Interactive Display

MW3565-T-X



Specifications

Model	MW3565-T-X	
Panel		
Backlight	DLED backlight	
Panel size	65 inches	
Resolution	3840*2160	
Brightness (cd/m²)	350	
Contrast ratio	1200:1	
Response time (ms)	8	
Color support	1.07 billion colors	
Viewing angle (H/V)	178°/178°	
Aspect Ratio	16:9	
Refresh Ratio	60HZ	
Android		
CPU architecture	GK6760V100	
CPU operating frequency	Octa-core A55_1.2GHz	
GPU	MailG52 MC2_600MHz	
RAM/ROM	DDR4: 8GB eMMC: 128GB	

1



Touch control Contactless IR sensor, supports 20-point touch Touch Accuracy (mm) 1 Glass Amm tempered glass, level 7 on Mohs hardness scale, anti-glare Response time (ms) 58 Input method Opaque objects (e.g. fingers, pens) Microphone Microphone Built in Microphone Distance 6 meter Interface Interface 2*HDMI IN [4K], 3*USB3.0, 2*USB 2.0, 2*touch USB, 1*Type C, 1*RJ45 IN, 1*SPDIF, 1*Earphone, 1*TF, 1*NS232, Power Button * 1 TTF, 1*NS232, Power Button * 1 Configuration Wi-FI 5, supports 5G/2.4G Performance 0*22m distance in open space NFC NFC Optional Sullt-in Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application spot 400 Support Windows, MAC, IOS, Android system Whiteboard Application spot 400 Sull amough be finally in Camera English (Multi-Language Support) VESA Well mount hole (mm) 500*400 General Power input AC 100 to 240V, 50/60Hz	System version	Android 12.0	
Touch Accuracy (mm)	Touch		
Glass 4mm tempered glass, level 7 on Mohs hardness scale, anti-glare Response time (ms) s8 Input method Opaque objects (e.g. fingers, pens) Microphone Microphone Built in Microphone Distance 6meter Interface ***THE*** I**R\$23.2*** Power Button ** 1 **THE*** I**R\$23.2*** Power Button ** 1 **THE*** I**R\$23.2*** Power Button ** 1 **Audio ***THE*** I**R\$23.2*** Power Button ** 1 **Audio*** **Peaker** 2×15W** WIFFI **Configuration Wi-Fi 5, supports 5G/2.4G** Performance 0**12m distance in open space NFC NFC Optional **Camera** **Buletooth** Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application Support SOS Language English (Multi-Language Support) VESA Wall mount hole (mm) \$00**400 General **THE*** In Microphone Bultin Microphone Distance Application and the service of the microphone **THE*** In Micro	Touch control	Contactless IR sensor, supports 20-point touch	
Response time (ms) s8 Input method Opaque objects (e.g. fingers, pens) Microphone Distance 6 meter Interface 2*HDMI INI(AK), 3*USB3.0. 2*USB2.0. 2*touch USB. 1*Type C. 1*RI45 IN. 1*SPDIF. 1*Earphone, 1*TF. 1*RS232. Power Button * 1 Audio WIFI Configuration WIFI 5, supports 5G/2.4G Performance 0*12m distance in open space NEC NEC Optional Camera 13MP Built-in Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application Support Windows, MAC, IOS, Android system Wistory Windows, Mac, IOS, Android system <td< td=""><td>Touch Accuracy (mm)</td><td>±1</td></td<>	Touch Accuracy (mm)	±1	
Input method Opaque objects (e.g. fingers, pens) Microphone Microphone Built in Microphone Distance 6 meter Interface Interface 2*HOMINI(4K), 3* USB3.0, 2*USB 2.0, 2*touch USB, 1* Type C. 1* RI45 IN, 1* SPDIF, 1* Earphone, 1* TF, 1*RS232, Power Button * 1 Audio ***Pepaker** Speaker** 2*15W WI-FI Configuration Wi-Fi 5, supports 56/2.4G Performance O*12m distance in open space NFC NFC NFC Optional Camera 13MP Built-in Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application Whiteboard Application Sos Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General **Terminate of meters** **Termina	Glass	4mm tempered glass, level 7 on Mohs hardness scale, anti-glare	
Microphone Built in Microphone Cistance 6 meter Cisteriace Cisteri	Response time (ms)	≤8	
Microphone Built in Microphone Distance 6 meter Interface Interface Interface 2*HDMI IN(4K), 3* USB3.0, 2*USB2.0, 2*touch USB, 1* Type C, 1* RJ45 IN, 1* SPDIF, 1* Earphone, 1* TF, 1*RS232, Power Button * 1 Audio Speaker 2×15W WI-FI Configuration Wi-Fi 5, supports 56/2.4G Performance 0*12m distance in open space NFC NFC Optional Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application support Whiteboard Application support OSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	Input method	Opaque objects (e.g. fingers, pens)	
Distance 6 meter Interface Interface 2*HDMI IN(4K), 3* USB3.0, 2*USB2.0, 2*touch USB, 1* Type C, 1* RI45 IN, 1* SPDIF, 1* Earphone, 1* TF, 1*RS232, Power Button * 1 Audio Speaker 2×15W Wi-FI Configuration Wi-Fi 5, supports 5G/2.4G Performance 0*12m distance in open space NFC NFC Optional Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application support Whiteboard Application support OSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	Microphone		
Interface 1* Interface 2* Inter	Microphone	Built in Microphone	
Interface 2*HDMI IN(4K), 3* USB3.0, 2*USB3.0, 2*USB2.0, 2*touch USB, 1*Type C, 1*RI45 IN, 1*SPDIF, 1*Earphone, 1*TF, 1*RS232, Power Button *1 Audio Speaker 2×15W Wi-Fi Configuration Wi-Fi 5, supports 5G/2.4G Performance 0*12m distance in open space NFC NFC NFC Optional Camera 13MP Built-in Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application support Whiteboard Application support Whiteboard Application support Whiteboard Mapplication support Whiteboard Mapplication support Sos Uanguage English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	Distance	6 meter	
Interface 1* TF, 1*RS232. Power Button * 1 Audio Speaker 2×15W Wi-Fi Configuration Wi-Fi 5, supports 5G/2.4G Performance 0*12m distance in open space NFC NFC Optional Camera 13MP Built-in Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application support OSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	Interface		
Speaker 2×15W Wi-Fi Configuration Wi-Fi 5, supports 5G/2.4G Performance 0°12m distance in open space NFC NFC Optional Camera Camera 13MP Built-in Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application Whiteboard Application Usual Support Windows, MAC, IOS, Android System Whiteboard Application Support Windows, MAC, IOS, Android System Support Windows, MAC, IOS, Android System Whiteboard Application Su	Interface		
Wi-Fi S, supports 5G/2.4G Performance 0°12m distance in open space NFC NFC Optional Camera Camera 13MP Built-in Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application support OSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500°400 General	Audio		
Configuration Wi-Fi 5, supports 5G/2.4G Performance 0°12m distance in open space NFC NFC Optional Camera Camera 13MP Built-in Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application Whiteboard Performance 15mg/stance 15mg	Speaker	2×15W	
Performance 0°12m distance in open space NFC NFC Optional Camera Camera 13MP Built-in Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application Whiteboard Application Whiteboard Application Support Suppo	Wi-Fi		
NFC Optional Camera Camera 13MP Built-in Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application support OSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	Configuration	Wi-Fi 5, supports 5G/2.4G	
NFC Optional Camera Camera 13MP Built-in Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application support OSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	Performance	0~12m distance in open space	
Camera 13MP Built-in Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application support CSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	NFC		
Camera 13MP Built-in Camera Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application support OSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	NFC	Optional	
Bluetooth Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application support OSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	Camera		
Version 5.0 Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application support OSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	Camera	13MP Built-in Camera	
Performance 12m transmission distance in open space Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application support OSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	Bluetooth		
Wireless Screen Mirroring System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application support OSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	Version	5.0	
System Support Windows, MAC, IOS, Android system Whiteboard Application Whiteboard Application support OSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	Performance	12m transmission distance in open space	
Whiteboard Application Whiteboard Application Support USD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	Wireless Screen Mirroring		
Whiteboard Application support OSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	System	Support Windows, MAC, IOS, Android system	
OSD Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	Whiteboard Application		
Language English (Multi-Language Support) VESA Wall mount hole (mm) 500*400 General	Whiteboard Application	support	
VESA Wall mount hole (mm) 500*400 General	OSD		
Wall mount hole (mm) 500*400 General	Language	English (Multi-Language Support)	
General	VESA		
	Wall mount hole (mm)	500*400	
Power input AC 100 to 240V, 50/60Hz	General		
	Power input	AC 100 to 240V, 50/60Hz	



Overall power consumption (W)	≤180 (without OPS)
Standby power consumption (W)	<0.5
Operating temperature	0°C to 40°C
Operating humidity	10% to 80% RH, non-condensing
Storage temperature	-20°C to 60°C
Storage humidity	10% to 90% RH, non-condensing
Product dimensions (W*H*D)(mm)	1483.8*902*115.8
Packaging dimensions (W*H*D)(mm)	1615.8*220*1028
Weight (kg)	Net weight: 45.5
	Gross weight: 56
Accessories included	1*power cable, $2*$ Touch Pen, $1*$ quick guide, $1*$ IR remote controller, $1*$ wall mounting bracket, $1*$ HDMI cable
LED Life	30000 hours or above
*Note	*The specifications listed above may vary with device model

Zhejiang Uniview Technologies Co., Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: overse as business@uniview.com; global support@uniview.com

http://www.uniview.com

 $\hbox{@2023 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.}$

^{*}Product specifications and availability are subject to change without notice.